

Log Cabin

Underground Railroad BOM - Month 5

A pattern by Mary Go Round Quilts



Fabric Needed:

3½" x 3½" square for center (Color A)

Finished size 12"
All seams ¼"

Dark Fabric

(1) 5" x 2" strip and (1) 3½" x 2" strip (Color B)

(1) 8" x 2" strip and (1) 6½" x 2" strip (Color D)

(1) 11" x 2" strip and (1) 9½" x 2" strip (Color F)


Light Fabric

(1) 6½" x 2" strip and (1) 5" x 2" strip (Color C)

(1) 9½" x 2" strip and (1) 8" x 2" strip (Color E)

(1) 12½" x 2" strip and (1) 11" x 2" strip (Color G)


1. Sew the 3½" x 2" dark strip (B) onto the 3½" center square (A). Press toward the dark. (Fig. 1)



(Fig 1)


2. Sew the 5" x 2" dark strip (B) to the left side of the block. (Fig. 2)

Note: For all remaining seams, press outward (away from center).




(Fig 2)

3. Sew the 5" x 2" light strip (C) to the bottom of the block. (Fig. 3)



(Fig 3)

4. Sew the 6½" x 2" light strip (C) to the right side of the block. (Fig. 4)



(Fig 4)

www.marygoroundquilts.com



@marygounquilts

Using the diagram below as a guide, continue building your log cabin block, sewing strips counter-clockwise.

5. Sew the $6\frac{1}{2} \times 2$ " dark strip (D) to the top. Then sew the 8×2 " dark strip (D) to the left. (Fig. 5)
6. Sew the 8×2 " light strip (E) to the bottom. Then sew the $9\frac{1}{2} \times 2$ " strip light strip (E) to the right. (Fig. 6)
7. Sew the $9\frac{1}{2} \times 2$ " dark strip (F) to the top. Then sew the 11×2 " strip dark strip (F) to the left. (Fig. 6)
8. Sew the 11×2 " light strip (G) to the bottom. Then sew the $12\frac{1}{2} \times 2$ " strip light strip (G) to the right. (Fig. 6)

